


FLANGE LAP JOINT A105 150 LBS RF

Tamaño nominal de la tubería	Ø exterior O	Mínimo espesor tf	Ø Buje X	Longitud con eje Y	Ø Mínimo agujero B	Ø · Radio R	Taladros			
							Ø K centro tal.	Número de tal	Ø alto. L	Ø Tornille
1/2	3.5	0,44	1.19	0,62	0,9	0,12	2,38	4	5/8	1/2
(DN15)	(90)	(11,2)	(30)	(16)	(22,9)	(3)	(60,3)		(15.875)	(12,7
3/4	3,88	0,5	1.5	0,62	1.11	0,12	2,75	4	5/8	1/2
(DN20)	(100)	(12,7)	(38)	(16)	(28.2)	(3)	(69,9)		(15.875)	(12,7
1	4.25	0,56	1,94	0,69	1,38	0,12	3.12	4	5/8	1/2
(DN25)	(110)	(14,3)	(49)	(17)	(34,9)	(3)	(79.4)		(15.875)	(12,7
1 1/4	4,62	0,62	2.31	0,81	1,72	0,19	3,5	4	5/8	1/2
(DN32)	(115)	(15,9)	(59)	(21)	(43,7)	(5)	(88,9)		(15.875)	(12,7
11/2	5	0,69	2,56	0,88	1,97	0,25	3,88	4	5/8	1/2
(DN40)	(125)	(17,5)	(65)	(22)	(50)	(6)	(98,4)		(15.875)	(12,7
2	6	0,75	3.06	1	2,46	0,31	4,75	4	3/4	5/8
(DN50)	(150)	(19,1)	(78)	(25)	(62,5)	(8)	(120,7)		(19.05)	(15.87
2 1/2	7	0,88	3,56	1.12	2,97	0,31	5,5	4	3/4	5/8
(DN65)	(180)	(22,3)	(90)	(29)	(75,4)	(8)	(139,7)		(19.05)	(15.87
3	7.5	0,94	4.25	1.19	3.6	0,38	6	4	3/4	5/8
(DN80)	(190)	(23,9)	(108)	(30)	(91.4)	(10)	(152,4)		(19.05)	(15.87
3 1/2	8.5	0,94	4.81	1.25	4.1	0,38	7	8	3/4	5/8
(DN90)	(215)	(23,9)	(122)	(32)	(104.1)	(10)	(177,8)		(19.05)	(15.87
4	9	0,94	5.31	1.31	4.6	0,44	7.5	8	3/4	5/8
(DN100)	(230)	(23,9)	(135)	(33)	(116.8)	(11)	(190.5)		(19.05)	(15.87
5	10	0,94	6.44	1.44	5,69	0,44	8.5	8	7/8	3/4
(DN125)	(255)	(23,9)	(164)	(36)	(144,4)	(11)	(215.9)		(22.225)	(19.0
6	11	1	7.56	1,56	6,75	0,5	9.5	8	7/8	3/4
(DN150)	(280)	(25,4)	(192)	(40)	(171,4)	(13)	(241.3)		(22.225)	(19.0
8	13.5	1.12	9.69	1,75	8,75	0,5	11,75	8	7/8	3/4
(DN200)	(345)	(28.6)	(246)	(44)	(222,2)	(13)	(298,5)		(22.225)	(19.0
10	16	1,19	12	1,94	10,92	0,5	14.25	12	1	7/8
(DN250)	(405)	(30,2)	(305)	(49)	(277,4)	(13)	(362)		(25,4)	(22.22
12	19	1,25	14.38	2.19	12,92	0,5	17	12	1	7/8
(DN300)	(485)	(31,8)	(365)	(56)	(328,2)	(13)	(431,8)		(25,4)	(22.22
14	21	1.38	15,75	3.12	14,18	0,5	18,75	12	1 1/8	1
(DN350)	(535)	(35)	(400)	(79)	(360,2)	(13)	(476,3)		(28,575)	(25,4
16	23,5	1,44	18	3.44	16.19	0,5	21,25	16	1 1/8	1
(DN400)	(595)	(36,6)	(457)	(87)	(411.2)	(13)	(539,8)		(28,575)	(25,4
18	25	1,56	19,88	3.81	18.2	0,5	22,75	16	1 1/4	1 1/8
(DN450)	(635)	(39,7)	(505)	(97)	(462.3)	(13)	(577,9)		(31,75)	(28,57
20	27,5	1,69	22	4.06	20,25	0,5	25	20	1 1/4	1 1/8
(DN500)	(700)	(42,9)	(559)	(103)	(514,4)	(13)	(635)		(31,75)	(28,57
24	32	1,88	26.12	4.38	24.25	0,5	29,5	20	1 3/8	1 1/-
(DN600)	(815)	(47,7)	(663)	(111)	(616)	(13)	(749,3)		(34,925)	(31,7



CONTÁCTANOS

- Lautaro 2083 2097 Lote 5, Concepción
- ventas@wenganindustrial.cl
- **S** +56 9 8731 4484





